



1520M

- Outside clamping 10"-21"
- 13" max width, 40" max diameter
- Swing arm tower
- 110V power
- ATV clamp set (EAA0332G84A) available to allow clamping down to 7" diameter

1520EMX

Adds assist arm



RC150

- Outside clamping 6"-23"
- 11.5" max width, 50" max diameter
- Swing arm tower
- 110V power
- Extended width clamp set available for use with up to 14" wide wheels
- Manual bead roller

RC200

Adds assist arm



2300M

- Wheel diameters of 8"-30"
- Max weight capacity - 155 lbs
- Max tire size of 21" W x 48" diameter
- LCD display
- 110V power
- 14mm motorcycle shaft
- Shaft adapter kits available for most shaft sizes
- **2000561:** Harley Kit 3/4" shaft and 1" bushings



775

- Wheel diameters of 8"-30"
- Max weight capacity - 100 lbs
- Max tire size of 20" W x 34" diameter
- LED display
- 110V power
- 40mm automotive shaft & cones to 5"
- **Parts required to make the 775 motorcycle compatible:**
- **5606376:** Motorcycle clamp adapter kit - 14mm
- Optional shaft adapter kits: (**560640701** shaft interface required to use either shaft kit)
- **5000648:** 3/4" shaft kit
- **5000248:** 1" shaft kit
- **5009164:** 25mm shaft kit



CH-22 MANUAL TIRE CHANGER

- Outside clamping 4"-16.5"
- Manual unit - no power required
- Clamp the CH-22 in your rim clamp machine to secure during use, or add the optional CH-23 bead breaker and stand (shown at right)
- Comes with CH-4 tire tool



CH-22



CH-22 / CH-23



MOTORCYCLE / ATV TIRE IRONS

- **T9A:** Double ended spoon, 9" long x 7/16" stock (32109)



- **T16A:** Double ended spoon, 16" long x 7/16" stock (32116)



- **T8:** 16" long x 7/16" stock, plastic handle (32118)

